

BRIGHTWELL

Datasheet



BrightLogic 2

The BrightLogic 2 is an on-premise laundry dosing system available in 2, 4, 6, 8 and 10 pump configurations.

The space-saving patented double pump head is easy to install and maintain thanks to the quick-tube-change configuration. Suitable for both intelligent and non-intelligent washing machines up to 35kg.



Technical Specifications

	2 Pump	4 Pump	6 Pump
Dimensions (mm)	285 x 190 x 166	266 x 285 x 166	266 x 425 x 166
Weight	2 kg	4 kg	5.5 kg
Power	36W	41W	71W
Current	0.4A (100V) - 0.14A (240V)	0.46A (100V) - 0.16A (240V)	0.8A (100V) - 0.27A (240V)

Technical specifications

Signal supply	12-240V AC or DC, Opto-isolated
Outputs	Flush Valve 24V DC, 1.25A (10W) max Buzzer/Lamp 24V DC 500Ma, (10W) max
Flowrate	70ml - 285ml/min*
Tube options	Silicone BrightChem
Motor	Brushless 24V DC, 600mA
Enclosure	Polypropylene, IP45



Installation kit	Available on request
Accessories	Formula Select Module Manifold (4/6 way) Pump Modules Low Level Alarm Suction Wands
Approvals	CE, UL
Warranty	2 years

In the box

Brightlogic Unit

Mounting Kit

Quickstart Guide

Formula Select (optional)

Part Numbers


WL# (number of pumps)

Brightlogic 2 Unit

*flow rate with water and 6mm BrightChem tube

BRIGHTWELL

Brightwell Dosing Ltd
Unit 1, Rich Industrial Estate
Avis Way, Newhaven
East Sussex, BN9 0DU

T: +44 (0)1273 513 566 
E: sales@brightwell.co.uk

© 2023 Brightwell Dosing Ltd | Registered in England, Number 00661996.

