

KNIGHTON K-PRO AUTO DISHWASH

Page: 1

Compilation date: 23/02/2018

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: KNIGHTON K-PRO AUTO DISHWASH

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Professional dishwash detergent

1.3. Details of the supplier of the safety data sheet

Company name: Knighton Janitorial

Unit 18, Willow Road

Trent Lane Industrial Estate

Castle Donington

DE74 2NP

Tel: 0845 301 0442

Email: sales@knightonjanitorial.com

1.4. Emergency telephone number

Emergency tel: 0845 301 0442

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1A: H314

Most important adverse effects: Causes severe skin burns and eye damage.

2.2. Label elements

Label elements:

Hazard statements:	H314: Causes severe skin burns and eye damag	
Hazard pictograms:	GHS05: Corrosion	



Signal words:	Danger
Precautionary statements:	P280: Wear protective gloves/clothing and eye/face protection.
	P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.
	Rinse skin with water.
	P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
	P310: Immediately call a.

KNIGHTON K-PRO AUTO DISHWASH

Haz. ingredients (label): SODIUM HYDROXIDE; TETRASODIUM ETHYLENE DIAMINE TETRAACETATE

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-573-9	64-02-8	-	Acute Tox. 4: H302; Eye Dam. 1: H318	10-30%
SODIUM HYDR	OXIDE			

215-185	-5	1310-73-2	-	Skin Corr. 1A: H314	1-10%	
---------	----	-----------	---	---------------------	-------	--

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin.
	Drench the affected skin with running water for 10 minutes or longer if substance is still
	on skin. Transfer to hospital if there are burns or symptoms of poisoning.
Eye contact:	Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist
	examination.
Ingestion:	Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10
	minutes. If unconscious, check for breathing and apply artificial respiration if necessary.
	If unconscious and breathing is OK, place in the recovery position. Transfer to hospital
	as soon as possible.
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. If
	unconscious and breathing is OK, place in the recovery position. If conscious, ensure
	the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and
	provide oxygen if available. Transfer to hospital as soon as possible.
4.2. Most important symptom	is and effects, both acute and delayed
Skin contact:	Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

- Eye contact: Corneal burns may occur. May cause permanent damage.
 - **Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.
- **Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.
- Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

KNIGHTON K-PRO AUTO DISHWASH

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

KNIGHTON K-PRO AUTO DISHWASH

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

SODIUM HYDROXIDE

Workplace exposure limits:		Respirable dust		
State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	2 mg/m3	2 mg/m3	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- State: Liquid
- Colour: Pale yellow

Odour: Characteristic odour

Viscosity: Non-viscous

Relative density: 1.19 - 1.21

pH: 13.1 - 13.6

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

KNIGHTON K-PRO AUTO DISHWASH

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

SODIUM HYDROXIDE

IPR	MUS	LD50	40	mg/kg
ORL	RBT	LDLO	500	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

- **Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.
- **Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

KNIGHTON K-PRO AUTO DISHWASH

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Marine pollutant: No

Section 14: Transport information

14.1. UN number

UN number: UN1719

14.2. UN proper shipping name

Shipping name: CAUSTIC ALKALI LIQUID, N.O.S.

(SODIUM HYDROXIDE)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 2

Section 15: Regulatory information

KNIGHTON K-PRO AUTO DISHWASH

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment		
Section 16: Other information		
Other information		
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No	
	2015/830.	
	* indicates text in the SDS which has changed since the last revision.	
Phrases used in s.2 and s.3:	H302: Harmful if swallowed.	
	H314: Causes severe skin burns and eye damage.	
	H318: Causes serious eye damage.	
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive	
	and shall be used only as a guide. This company shall not be held liable for any	
	damage resulting from handling or from contact with the above product.	