Revision Date: 08/12/2005

# SAFETY DATA SHEET



#### SELCLEN S F014

#### IDENTIFICATION OF THE PREPARATION AND COMPANY

PRODUCT CODE: F014 PRODUCT NAME: SELCLEN S

MANUFACTURER: Selden Research Limited

> Staden Lane Ashbourne Road

**Buxton** Derbyshire SK17 9RZ

TELEPHONE: 01298 26226 FAX: 01298 26540

EMAIL: safety@selden.co.uk

. COMPOSITION/INFORMATION ON INGRE	DIENTS		
NAME			
CAS No.:	EINECS Nr.:	CLASSIFICATION	CONTENT
ALCOHOL ETHOXYLATE			
		Xi;R38,R41.	1-5 %
ALCOHOL ETHOXYLATE			
		Xi;R38,R41.	1-5 %
ANIONIC SURFACTANT			
		Xi;R36/37/38.	1-5 %
SODIUM HYDROXIDE			
215-185-5	1310-73-2	C;R35	1-5 %
SODIUM SILICATE			
215-687-4	1344-09-8	Xi;R38,R41.	1-5 %
TRISODIUM NITRILO TRIACETE (40% ACTIVE)			
	5064-31-3	Xi;R36.	10-30 %

### HAZARDS IDENTIFICATION

# R38 Irritating to skin., R41 Risk of serious damage to eyes

#### 4. FIRST AID MEASURES

INHALATION: Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if

any discomfort continues.

Remove victim immediately from source of exposure. DO NOT INDUCE VOMITING!, Rinse mouth thoroughly. Drink plenty of water. Get medical attention. INGESTION:

Remove affected person from source of contamination. Remove contaminated clothing. Rinse the skin SKIN:

immediately with lots of water. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing.

EYES: Hold eyelids apart. Important! Immediately rinse with water for at least 15 minutes. Get medical

attention immediately. Continue to rinse

5. FIRE FIGHTING MEASURES

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials. Use:, EXTINGUISHING MEDIA:

Dry chemicals, sand, dolomite etc. Foam. Water spray

SPECIAL FIRE FIGHTING PROCEDURES: Use water to keep fire exposed containers cool and disperse vapours.

6. ACCIDENTAL RELEASE MEASURES

Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. SPILL CLEAN UP METHODS:

Flush with plenty of water to clean spillage area.

Any spillage needs to be contained and not allowed to enter water courses **ENVIRONMENTAL PRECAUTIONS:** 

7. HANDLING AND STORAGE

**USAGE PRECAUTIONS:** Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS: Store in tightly closed original container in a cool, dry well-ventilated place. Keep in original container.

> **SELCLEN S** F014 Revision Date: 08/12/2005

Page 1 of 3

F014

SELCLEN S

Revision Date:

## 08/12/2005

# SAFETY DATA SHEET



#### SELCLEN S F014

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

ST EXP 15 Min INGREDIENT NAME: CAS No.: STD LT EXP 8 Hrs

SODIUM HYDROXIDE WEL

PROTECTIVE EQUIPMENT:





#### 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear, Liquid Green COLOUR: ODOUR: Citrus DENSITY/SPECIFIC GRAVITY(g/ml) 1.073 - 1.083 pH-VALUE, CONC. SOLUTION:

SOLUBILITY: Soluble in water

10. STABILITY AND REACTIVITY

Stable under normal temperature conditions. STABILITY:

13.5

HAZARDOUS COMPOSITION PRODUCTS: Fire or high temperatures create:, Toxic gases/vapours/fumes of:, Carbon dioxide (CO2). Carbon

monoxide (CO).

11. TOXICOLOGY INFORMATION

May cause irritation to the respiratory system. INHALATION:

INGESTION: Liquid irritates mucous membranes and may cause abdominal pain if swallowed. May cause stomach

pain or vomiting.

SKIN CONTACT: Irritating to skin. Prolonged or repeated exposure may cause severe irritation.

EYE CONTACT: Risk of serious damage to eyes. Irritation of eyes and mucous membranes.

12. ECOLOGICAL INFORMATION

ECOTOXICITY: Not classed as Hazardous to the Environment but release to the environment should be avoided.

13. DISPOSAL CONSIDERATIONS

Dispose of waste and residues in accordance with local authority requirements. **DISPOSABLE METHODS:** 

> **SELCLEN S** F014 Revision Date: 08/12/2005

F014

SELCLEN S

Revision Date: 08/12/2005

# SAFETY DATA SHEET



#### SELCLEN S F014

#### 14. TRANSPORT INFORMATION

#### LABEL FOR CONVEYANCE:



UN No ROAD: 1760 UK ROAD TRANSPORT CLASS: 8 UK ROAD PACK GR.: Ш ADR CLASS NO .: R

ADR CLASS: Class 8: Corrosive substances.

PROPER SHIPPING NAME I: CORROSIVE LIQUID, NOS (Sodium hydroxide, Sodium metasilicate)

UN No SEA: 1760 IMDG CLASS: 8 UN NO. AIR: 1760

## 15. REGULATORY INFORMATION

#### LABEL FOR SUPPLY:



**RISK PHRASES:** R38 Irritating to skin. R41 Risk of serious damage to eyes.

SAFETY PHRASES: S2 Keep out of the reach of children, S23 Do not breathe vapour/spray. S24/25 Avoid contact with skin

and eyes. S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S37/39 Wear suitable gloves and eye/face protection. S46 If swallowed, seek medical advice immediately and show this container or label. S51 Use only in well-ventilated areas. S28 After contact with skin, wash immediately with plenty of water.

STATUTORY INSTRUMENTS: Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

Classification and Labelling of Substances and Preparations Dangerous for Supply. APPROVED CODE OF PRACTICE:

Workplace Exposure Limits EH40. CHIP for everyone HSG(108). **GUIDANCE NOTES:** 

**DETERGENT LABELLING:** 

< 5% Perfumes

< 5% Anionic surfactants

5-15% Non-ionic surfactants

5-15% NTA (nitrilotriacetic acid) and salts thereof

# 16. OTHER INFORMATION

**USER NOTES:** The following risk phrases relate to the raw materials in the product and not the product itself:-**REVISION DATE:** 08/12/2005

REV. NO./REPL. SDS GENERATED: 8

R-PHRASES (Full Text):

R35 Causes severe burns. R38 Irritating to skin., R41 Risk of serious damage to eyes. R36 Irritating to eyes. R36/37/38 Irritating to eyes, respiratory system and skin. R38 Irritating to skin., R41 Risk of serious damage to eyes. R38 Irritating to skin., R41 Risk of serious damage to eyes.

SELCLEN S F014 Revision Date: 08/12/2005