



A008 : Selseal

acrylic base coat seal

Description of product

Non-yellowing polymer film. Does not discolour even the lightest floor. Penetrates and seals porous floors, provides an ideal base for emulsion application. Resistant to polish strippers.

Product Uses

For all linoleum, P.V.C., rubber, terrazzo and thermoplastic floors. N.B. Do not use on unsealed wood and cork floor coverings.

Directions

Selseal must be applied to a clean grease free floor. Apply a thin even film of seal using a clean lint free mop or applicator. Apply a second coat when the first is dry (approximately 30 mins). **COVERAGE:** 50 square metres per litre. **MAINTENANCE:** Selseal is formulated as a sealer coat and does not have a high resistance to wear. It must be finished by the application of Selexel or other metallised polymer emulsion and normal maintenance techniques employed. **PROTECT FROM FROST. FOR PROFESSIONAL USE ONLY.**

iNsight Supported

iNsight is Selden's interactive product selection and training system. Enables the user to create full COSHH training kits, wallcharts, task cards and more. visit <http://www.selden.co.uk/insight>



iNsight recommended product uses

Flooring - pre-sealing (semi permanent)	typical dilution
	neat

Product Hazards and PPE Requirements

Contains : Benzisothiazolinone

Risk Phrases
Contains Benzisothiazolinone. May produce an allergic reaction.

Safety Phrases

Technical Data

Composition A blend of acrylic copolymers, resins incorporating wetting agents and film forming aids in a stable water based emulsion

Appearance Translucent emulsion

Colour White

Viscosity <10 cps

Density 1.012

pH 8.0 - 9.0

Activity 16%

Fragrance Characteristic slightly sweet

Stability 2 years in a unopened container

Storage Protect from freezing

Environmental Profile

Biodegradability
All surfactants contained in Selden Products meet the requirements of the EU Detergent Directive 2005 – 2004/648/EC. This requires all surfactants to break down both quickly and completely into harmless material such as CO2 and water.

Selden Environmental Charter

- We set ourselves industryleading standards.
- Selden minimises wastage, packaging and transportation.
- If it can be recycled, it will be recycled.
- Our chemicals policy exceeds regulatory requirements.
- We don't expect other people to clean up after us.
- Conserving energy, preserving resources.
- By being innovative, we strive to do better.
- We like to work in partnership with our clients.

Visit our website for more information.

External Accreditations

9001 - Quality System
14001 - Environmental System
18001 - Health & Safety System
IPPC Certified Manufacturer

Sustainability
Product conforms with the DEFRA endorsed Sustainable Cleaning guidance



COSHH+ Supported

Selden's bespoke COSHH awareness and product training tool. Users specify the products in use and instantly generate a full training pack to enable quick and effective staff training.



www.flagship-mcp.com

Flagship products are those products that are included in Selden Multi-language Cleaning Programme. Flagship products have induction kits, best practise guidance, MSDS, wallcharts and usage guides available in the following languages

english, french, spanish, portuguese, polish, german, dutch, russian, romanian, estonian, czech, croatian.



UKAS
accredited testing
laboratory No. 4204



SELDEN
formulating
testing
manufacturing
to
the highest
standards

Selden Research Limited

Staden Business Park, Staden Lane, Buxton
Derbyshire. SK17 9RZ

Tel : 01298 26226 | Fax : 01298 26540 | Email : info@selden.co.uk | web : www.selden.co.uk

